



# Generator Scout

Monitor System for Generators

## OVERVIEW

The Generator Scout monitor system is part of a family of proven remote monitor and control products offered by Advantis. This unit uses the same hardware as the Pump Scout series but has been specifically programmed to easily install and operate for backup generators - large or small.

The unit monitors digital and analog inputs and reports them to the secure Advantis Web Application via cellular. Alarms are immediate and reports are daily. The user controls alarm destinations - text or email. Daily reports indicate run time and/or other designated accumulators.

## BENEFITS

This proven system eases the users mind. The smart field processor will let you know when your generator needs attention - 24/7.

All alarms are immediate and have two messages - Red (out of normal) and Green (back to normal). Daily reports keep up with operating parameters that you choose.

## FEATURES

- 6 Digital In
- 3 Analog In
- Simple install and no field programming required
- Works with various types of sensors
- GSM cellular Coverage
- Can be customized
- Optional remote control available

11/04/2011 09:55	power up 04.00.00	
11/04/2011 09:56	General on	
11/04/2011 09:56	normal report	
11/04/2011 09:56	General off	
11/04/2011 10:05	General on	
11/04/2011 10:06	General off	
11/05/2011 00:00	normal report	
11/06/2011 00:00	normal report	
11/07/2011 00:00	normal report	
11/08/2011 00:00	normal report	
11/08/2011 09:00	Generator on	
11/08/2011 09:25	Generator off	00:25:04

## Generator Activity Report

## HOW IT WORKS

The Generator Scout comes in a small enclosure along with a cellular modem. The enclosure can be mounted or allowed to set in the bottom of an existing enclosure. After supplying power from the generator battery the unit immediately sends in a power up message to the Advantis Web App. Next, choose the digital inputs and connect wires for contact closure for desired events. Analog may be DC volts or 4-20mA.

The Web Application is secure and provides unlimited number of users. The Administrator enters label names for each chosen input that shows on alarms and reports. Destination email and text addresses are entered as well.